

4 Port PCI RS232 Serial Adapter Card with 16550 UART

StarTech ID: PCI4S550N



The PCI4S550N 4-port PCI Serial card turns an available PCI slot into four RS232 serial ports - a cost-effective solution for connecting any new or old serial peripheral, with support for data transfer rates of up to 115Kbps.

The PCI Serial card is a perfect solution for connecting serial modems, POS devices, PDAs, digital cameras, printers, ISDN terminal adapters and more, to your system without having to upgrade your peripheral devices for compatibility with newer standards (e.g. USB).

Saving time and hassle, the Serial PCI card is plug-and-play ready, and can be installed in minutes, supporting Windows® 7, Server 2008 R2, Vista, XP, ME, 2000, 98, 95, NT4, 3.1, DOS® and Linux® operating systems. Plus, the serial card offers IRQ sharing to help ensure stability and consistent performance, guaranteeing convenient, hassle-free connections.

Backed by a StarTech.com lifetime warranty and free lifetime technical support.



Applications

- **Manufacturing** (CNC machinery, process control equipment, bar code scanners, serial printers)
- **POS** (credit/debit card readers, receipt printers, bar code scanners, cash registers, scales)
- Consumer (modems, PDAs, digital cameras, printers)
- **Security** (UPS control, access key panels, video cameras, card readers, modems)
- Casino (video lottery terminals, slot machines)
- Environmental Control (lighting, temperature, clocks)
- **Hospital** (patient monitoring equipment, nurses' stations, modems)
- Hotel Front Desk (serial printers, bar code scanners, keyboard, mouse, receipt printer, credit/debit card reader)
- Hospitality/Restaurant (credit card/debit card reader, serial printers)
- ISDN Networking

Features

- Supports the RS-232 serial interface
- Includes drivers for Linux® and all versions of Windows®
- IRQ sharing saves resources and eliminates conflicts
- 16 byte FIFO buffer ensures fast data transfer while multitasking
- 5, 6, 7, 8-bit characters selection
- Even, odd, no parity, or force parity generations





Technical Specifications

Warranty Lifetime
FIFO 32 Bytes
Max Baud Rate 115.2 Kbps
Serial Protocol RS-232

Bus Type PCI / PCI-X (5 / 3.3V)

Card Type Standard Profile

Chipset ID ASIX/MosChip - MCS9845CV

Industry PCI 2.1

Standards

Interface Serial

Port Style Integrated on Card

Ports 4

Connector 1 - PCI / PCI-X (Universal 3.3 & 5V; 32-bit) Male

Type(s)

External Ports 4 - DB-9 (9 pin; D-Sub) Male

OS Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), XP Embedded, POS Ready

Compatibility 2009, Embedded System 2009, CE 5.0/6.0, 2000, 98SE, 95, DOS

Windows Server® 2012, 2008 R2, 2003

Linux

Product Height 4.7 in [120 mm]
Product Length 4.7 in [120 mm]
Product Weight 7.2 oz [204 g]
Product Width 0.8 in [20 mm]
Humidity 5~85% RH

Operating 0°C to 70°C (32°F to 158°F)

Temperature

Storage -40° C to 85° C (-40° F to 185° F)

Temperature

Shipping 0.5 lb [0.2 kg]

(Package) Weight

Included in 1 - 2 Port PCI 16550 Serial Card

Package

Included in 1 - Bracket with 2 DB9 Ports

Package





Included in

1 - Driver CD

Package

Included in

1 - User Manual

Package

Certifications, Reports and Compatibility







