

USB 3.0 to DVI External Video Card Multi Monitor Adapter with 1-Port USB Hub – 1920x1200

StarTech ID: USB32DVIEH



The USB32DVIEH USB 3.0 to DVI Adapter turns an available USB 3.0 port into a DVI output port with high resolution 1920x1200 video support. The adapter features built-in USB 3.0 pass-through, which offers a connection port in place of the USB port used for connecting the DVI adapter – an ideal workaround for Ultrabook™ or laptop users where only a limited number of USB ports are available.

The USB to DVI adapter functions as an external graphics card, providing a convenient way to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0). The included DVI to VGA adapter also allows you to use this device with a VGA display.

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your DVI display / projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher



Applications

- The 1-Port USB hub allows the use of another USB device without losing USB connectivity on your Utlrabook or slim laptop
- Add a secondary DVI display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- Run multiple applications on different screens check your email on one display and search the web on the other
- View large or multiple spreadsheets across multiple displays
- Use the adapter to connect your PC to your DVI-equipped projector or display for viewing family pictures and movies
- Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other

Features

- Supports resolutions up to 1920x1200
- Built in 1-Port USB 3.0 Hub
- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Quick, easy installation
- USB-powered No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the use of multiple USB32DVIEH adapters on a single system (up to 5)
- DVI to VGA adapter included





Technical Specifications

2 Years Warranty Audio No

USB Pass-Through Yes

16MB DDR II Memory

Industry Standards SuperSpeed USB 3.0, USB 2.0

Chipset ID MCT Trigger 5 T5-302 Output Signal DVI-I (DVI Digital/Analog)

Connector A 1 - USB 3.0 A (9 pin; SuperSpeed) Male

Connector B 1 - DVI-I (29 pin) Female

Connector B 1 - USB 3.0 A (9 pin; SuperSpeed) Female

Maximum Analog

1920x1200

Resolutions

1920x1200 Maximum Digital

Resolutions

Supported Resolutions Widescreen(16/32 bit):

1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800,

1280x768, 1280x720

Standard(16/32 bit):

1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600

Wide Screen Supported

Windows 8/8.1 (32/64) OS Compatibility

Yes

Windows 7(32/64) Windows Vista (32/64) Windows XP (32/64)

Drivers are WHQL certified

Microsoft WHQL Certified Yes

System and Cable CPU: i3 Dual core 2.8GHz Requirements RAM: 2GB or higher

Full HD Video:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Connect a maximum of five USB32DVIEH adapters on a single PC - See manual for Note

system requirements

Color Black





Hard-to-find made easy®

Enclosure Type	Plastic
Cable Length	6.3 in [160 mm]
Product Length	3.3 in [85 mm]
Product Width	1.9 in [49 mm]
Product Height	0.7 in [17 mm]
Product Weight	2.6 oz [75 g]
Power Source	USB-Powered

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -10°C to 75°C (14°F to 167°F)
Humidity < 85% non-condensing

Humidity < 85% non-condens Shipping (Package) 8.2 oz [233 g]

Weight

Included in Package 1 - USB 3.0 to DVI Adapter Included in Package 1 - DVI to VGA adapter

Included in Package 1 - Software CD

Included in Package 1 - Manual

Certifications, Reports and Compatibility











