

2x2 HDMI Matrix Switch - 4K with Fast Switching and Auto-Sensing

StarTech ID: VS222HD4K



Save time and hassle by automatically switching between your HDMI audio/video sources. This 2x2 HDMI® matrix switcher provides the ultimate viewing experience, with support for Ultra HD 4K. It lets you connect two HDMI sources to two HDMI displays, with exceptional 4K resolution, while switching seamlessly between your video sources.

Impressive image quality with 4K support

The matrix switch supports Ultra HD 4K picture quality on two monitors while switching between content from HDMI source devices - including Blu-ray™ players or DVD players, computer systems, video game consoles, digital cable or satellite boxes, and A/V receivers.

4K support ensures a higher level of image clarity and visibility, delivering four times the resolution of 1080p - 8.29 million pixels versus 2.07 million pixels. It provides a more engaging visual experience for audiences in a wide range of venues including conference centers, boardrooms, educational facilities, and commercial settings. With its exceptional image quality, 4K resolution is also ideal for bringing your digital signage to life.

Fast and versatile switching options

Enjoy hassle-free operation with four different switching modes:

- **Matrix switching:** lets you route either HDMI source (Input 1 or Input 2) to either monitor (Output 2 or Output 3) - and independently switch two displays between two video sources.
- **Fast auto-switching:** ensures minimal time for switching between HDMI sources. The switch provides effortless operation with advanced auto-sensing - it detects the latest connected HDMI source and automatically switches both outputs to that device. It also ensures no downtime in a digital signage application if a source signal is accidentally powered off or fails.

- **Priority switching:** identifies the first port to have first priority for HDMI sources, which will be output on both displays.
- **Manual switching:** enables you to manually select your HDMI source with front-panel buttons that are easy to use.

An IR remote control is included in the box, enabling you to select your desired input source remotely. The RS-232 serial control interface ensures easy remote operation with serial control enabled devices.

Hassle-free setup with plug-and-play installation

The matrix switch is easy to install. EDID emulation saves you time during setup by ensuring all of your display settings, such as native resolution and refresh rate, are communicated between your display and video source devices. The built-in EDID copy feature maximizes compatibility with your 4K display, to ensure a convenient plug-and-play installation and the sharpest image quality.

The VS222HD4K is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Applications

- Run Ultra HD 4K multimedia presentations on two monitors in conference rooms, commercial settings or at trade shows
- Switch between different video sources on your digital signage displays in hospitals, shopping centers, or schools
- Connect and switch between two video sources and two displays on a test bench, for troubleshooting computers
- Automatically switch between your Blu-ray player, set-top box, or gaming console in a home theatre environment

Features

- Impressive image quality with support for Ultra HD 4K
- Easy operation with automatic, priority and manual switching between HDMI sources
- Access two HDMI source devices on two independent HDMI displays, with 2 x 2 matrix switching
- IR remote control included
- RS-232 serial control interface
- EDID copy support ensures accurate display output
- Backward compatible with high-definition 1080p
- Mounting hardware included

Technical Specifications

Warranty	2 Years
Audio	Yes
Industry Standards	HDMI 1.4
Output Signal	HDMI
Ports	2
Audio Specifications	7.1 Surround sound
Maximum Digital Resolutions	4K @ 30 Hz
Supported Resolutions	3840x2160 (4K) 2560x1600 1920x1200 1920x1080 (1080p) 1280x720 (720p)
Wide Screen Supported	Yes
Connector A	2 - HDMI (19 pin) Female
Connector B	2 - HDMI (19 pin) Female
Connector B	1 - RJ-11 Female
LED Indicators	2 - Active port LED
LED Indicators	1 - Power LED
Input Voltage	100 ~ 240 AC
Output Current	1.5
Output Voltage	12 DC
Power Source	AC Adapter Included
Humidity	0% ~ 80%
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Color	Black
Product Height	0.8 in [20 mm]
Product Length	6.1 in [156 mm]
Product Weight	10.5 oz [298 g]
Product Width	2.6 in [65 mm]
Shipping (Package) Weight	2.3 oz [65 g]
Included in Package	1 - 2x2 HDMI matrix switch
Included in Package	1 - remote control
Included in Package	1 - universal power adapter (NA/EU/UK/AU)

Included in Package	1 - RJ11 cable (1200mm)
Included in Package	1 - RJ11 to DB-9 serial adapter
Included in Package	1 - mounting kit
Included in Package	1 - quick start guide

Certifications, Reports and Compatibility

