

## Gigabit Fiber SFP Transceiver Module - Cisco GLC-SX-MM Compatible - MM LC - 550m - 10 Pack

StarTech ID: *GLCSXMM10PST*



Perfect for large-scale deployments or installations on multiple devices, this bulk pack of Gigabit fiber SFP transceivers provides maximum cost savings. Built to exacting specifications and fully tested to ensure maximum performance, these high-quality transceiver modules can be installed into Cisco® switches and routers that support the GLC-SX-MM transceiver module, as well as other major brands of networking equipment.

The SFP transceivers provide a dependable and cost-effective way to add, replace or upgrade the Gigabit fiber ports on your 1000Base-SX networking equipment, backed by a lifetime warranty.

### **Built for reliable network performance**

The multimode SFP transceivers included in this 10-pack are manufactured by StarTech.com to meet or exceed OEM specifications and comply with the industry's MSA (Multi-Source Agreement) standards. Committed to the highest standards of quality, StarTech.com provides an extensive range of networking products including copper and fiber network cards, fiber media converters, Ethernet switches and wireless products.

### **Fully compatible with Cisco and other major brands**

These Gigabit multimode SFPs are engineered to the highest quality standards and are 100% Cisco compatible, equivalent to the Cisco GLC-SX-MM SFP transceiver. StarTech.com SFP transceivers are configured and fully tested to ensure they work seamlessly with Cisco or other major brands of networking equipment.

You can be assured that the use of StarTech.com SFP products should not affect the warranty protection of your networking equipment.

### **Convenient and scalable**

Delivering both convenience and scalability, these fiber transceivers are fully hot-pluggable, which enables you

to install them without interrupting network traffic or having to reboot your equipment. They provide a versatile and cost-effective solution that's compatible with a multitude of Gigabit networking devices.

Ideal for use in switches, routers and other networking equipment, the SFPs provide reliable performance, enabling you to expand your network to remote segments cost-effectively. The multimode SFPs have a maximum distance of up to 550 m (1804 ft.) and maximum data rates of up to 1.25Gbps.

You can count on GLCSXMM10PST for reliable performance, backed by a lifetime warranty and free lifetime technical support.

### **Applications**

- Replace defective or damaged SFPs in MSA compliant or Cisco equipment
- Ideal for deployment in network devices with multiple SFP slots
- Expand your network to remote segments

### **Features**

- Delivers reliable Gigabit Ethernet connections for 1000Base-SX compliant networks
- 100% Cisco compatible, equivalent to GLC-SX-MM
- Backed by lifetime warranty and free lifetime technical support
- Meets or exceeds OEM specifications and MSA (Multi-Source Agreement) industry standards
- 850 nm optical wavelength
- Multimode with maximum distance of up to 550 m (1804 ft.) and LC fiber connector
- Maximum data rates up to 1.25Gbps
- Hot-pluggable

Technical Specifications

|                               |  |
|-------------------------------|--|
| Warranty                      | Lifetime   |
| Industry Standards            | IEEE 802.3z 1000BASE-SX  |
| WDM                           | No   |
| Compatible Networks           | 1000 Mbps (1 Gbps)   |
| DDM                           | No   |
| Fiber Operating Mode          | Half/Full-Duplex   |
| Fiber Type                    | Multi Mode   |
| Max Transfer Distance         | 550 m (1804 ft)  |
| Maximum Data Transfer Rate    | 1.25 Gbps  |
| Wavelength                    | 850nm  |
| Local Unit Connectors         | 1 - Fiber Optic LC Duplex Female                                   |
| <b>Note</b>                   | For use in Gigabit fiber networking equipment and media converters |
| System and Cable Requirements | MSA or Cisco compliant SFP port                                    |
| Humidity                      | 5~95% RH   |
| Operating Temperature         | 0°C to 70°C (32°F to 158°F)  |
| Storage Temperature           | -40°C to 85°C (-40°F to 185°F)                                     |
| Color                         | Silver   |
| Enclosure Type                | Zinc-Plated Casing   |
| Product Height                | 0.5 in [12 mm]   |
| Product Length                | 2.2 in [57 mm]   |
| Product Weight                | 0 lb [0 kg]  |
| Product Width                 | 0.5 in [13 mm]   |
| Shipping (Package) Weight     | 7.6 oz [214 g]   |
| Included in Package           | 10 - SFP transceivers  |

Certifications, Reports and Compatibility

 RoHS Compliant  
Available

