



Epson TM-T88VI

Reliable, ultra-fast reciept printer with state of the art mobile connectivity

Connect to multiple devices simultaneously

Ultrafast print speed of up to 350 mm/s

Reliability you can count on

Easy printing from mobile devices

Print from web-based applications

Triple interface connectivity to future proof growing businesses

Epson TM-T88VI

Product Specifications			
PAPER		COLOUR	Black / White
PAPER SIZE	80mm: 79.50 ± 0.50 (W) mm x dia 83.00 mm	INSTALLATION	Horizontally, wall hanging
	58 mm: 57.50 ± 0.50 (W) mm x dia 83.00 mm	INTERFACE CONNECTORS	D.K.D. function
FONTS & STYLES		HUMIDITY	Operation 10% - 90%
PRINT SPEED	350 mm/s	TEMPERATURE	Operation 5° C - 45° C, Storage -10° C - 50° C
PRINT SPEED (DEFAULT)	300 mm/s	STANDARD COMPLIANCE	
PRINTING FONT	Font A (default): 12 x 24 Font B: 9 x 17 (including 2-dot horizontal spacing)	SAFETY APPROVALS	RCM: AS / NZS CISPR class A Energy-saving: ENERGY STAR
COLUMN CAPACITY RECIEPT	80mm: 42/48/56 columns	OTHER	
	58mm: 30/36/40 columns	WARRANTY	48 months
CHARACTER SIZE	Font A: 1.41 x 3.39 (W x H mm)	WHAT'S IN THE BOX	
	Font B: 0.99 x 2.40 (W x H mm)		Connector cover
CHARACTER SET	95 Alphanumeric, 18 set International, 128 x 43 Graphic		Main unit
PRINTING CHARACTERS	Text (incl. Euro symbol), Graphics, Barcode		PS-180 & AC cable
INTERFACES	D 'II ' 110D D 'II ' 5II 1 140400D TTT\		Paper spacer
CONNECTIVITY	Built-in USB, Built-in Ethernet (10/100Base-T/TX) +		Power switch cover
	UIB (Serial, Parallel, Powered USB) Bluetooth 2.1+EDR (dedicated model)		Roll paper
	Wireless (USB wireless dongle): 0T-WL05 (802.11		Setup guide
	a/b/g/n) or OT-WL02 (802.11 b/g/n)	OPTIONAL ACCESSORIES	Warranty document
	Beacon (using Bluetooth low energy): Beacon dongle	C32C845040	WH-10 (040) Wall hanging bracket
	(Epson approved dongle: Laird model BT-820)	C32C890739	OT-WL02 (739): Wireless LAN Dongle, 2.4 GHz
DATA BUFFER	(Epoor approved donglo: Earla model D1 020)	C32C814596	Power supply cover
DATA BUFFER	45 Bytes or 4 kb, selectable	CONFIG BUILDS	1 Ower supply cover
POWER		C31CE94241	TM-T88VI-241 Built-in ethernet, USB, serial,
POWER SUPPLY	PS-180, AC cable	0010201211	dark grey
OPERATING VOLTAGE	24 V	C31CE94243	TM-T88VI-243 Built-in ethernet, USB, parallel,
POWER CONSUMPTION	Operating: 27.6W		gark grey
	Stand by: 0.5W	C31CE94581	TM-T88VI-581 Built-in ethernet, USB, BT:0S
GENERAL			dark grey
PRODUCT DIMENSIONS	145 x 195 x 148 mm (Width x Depth x Height)	COVER PLUS (OPTION)	
PRODUCT WEIGHT	1.6 kg	1YWT88VI	CoverPlus 1yr service pack TM-T88VI

Better Products for a Better Future













Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON AUSTRALIA

3 Talavera Road North Ryde NSW 2113 Tel: (02) 8899 3666 www.epson.com.au ABN 91 002 625 783

EPSON NEW ZEALAND

Level 2 7-9 Fanshawe Street Auckland, 1010 Tel: 0800 443 478 www.epson.co.nz

06/17



