



## RMCARD205 Remote Management Card

Remotely manage, monitor and control your UPS or ATS PDU from a web browser or SNMP management application.

The CyberPower RMCARD205 is a full-featured network UPS management device that remotely manages, monitors, and controls CyberPower UPS systems and ATS PDU products.

The internal card allows remote monitoring and control of a UPS via Web Browser, CLI, or NMS connection. By utilizing the auto-shutdown software, servers and workstations stay protected from data loss due to power failure. An optional Environmental Sensor (ENVIROSENSOR) can be added to monitor ambient temperature and humidity.

The firmware can be updated by users to insure you have the latest features and updates.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

### Features

- Real time UPS monitoring
- Supports environment sensor
- Remote management and configuration of UPS and ATS PDUs via Web Browser, CLI (Telnet or SSH), or NMS (SNMPv1 or v3)
- Automatic events notification via Email, SMS, SNMP Traps, and Syslog
- Logging of Events, Status Records
- Supports RADIUS, LDAP, LDAPS, and Windows Active Directory external authentication protocols
- User upgradeable firmware
- Allows configuration and updating of multiple units at once
- Compatible with select Smart App UPS and ATS PDUs\*

# RMCARD205 Remote Management Card

Remotely manage, monitor and control your UPS from a web browser or SNMP management application.

GENERAL	
Type	Network Management Card
COMMUNICATION	
Protocols	IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPS, SSH, SSL, TLS
Network Connection	RJ45 - 10/100Mbps Ethernet
PHYSICAL	
Dimensions (WxHxD) (in.)	1.61 x 1.42 x 3
Dimensions (WxHxD) (mm.)	40.89 x 36.06 x 76.2
Weight (lbs.)	0.08
Weight (kg.)	0.04
SHIPPING DIMENSIONS	
Dimensions (WxHxD) (in.)	6.8 x 2.4 x 6.5
Dimensions (WxHxD) (mm.)	172 x 60 x 165
Weight (lbs.)	0.35
Weight (kg.)	0.16
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	14°F to 122°F / -10°C to 50°C
Storage Relative Humidity	0% - 95% non condensing
Storage Elevation	0-50000 feet (0-15000 meters)
COMPATIBILITY	
UPS Models	Select OL Series UPS, OR/PR Series UPS, and ATS PDUs with an Expansion Slot*
CERTIFICATIONS	
Safety	FCC Class A, CE
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited