



## SRV3KI



High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions

Includes: CD with software, USB cable, User Manual

## Technical Specifications

### Output

Output power capacity	2.4kWatts / 3.0kVA
Max Configurable Power (Watts)	2.4kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(6) IEC 320 C13 (Battery Backup) (1) IEC 320 C19 (Battery Backup)

### Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 280V
Number of Power Cords	1
Other Input Voltages	220, 240

### Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4hour(s)
Efficiency	View Efficiency Graph

### Communications & Management

Control panel	Multi-function LCD status and control console	<a href="#">Back to top</a>
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous	

## Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

## Physical

Maximum Height	336MM, 33.6CM
Maximum Width	190MM, 19.0CM
Maximum Depth	425MM, 42.5CM
Net Weight	26.8KG
Shipping weight	29.0KG
Shipping Height	465MM, 46.5CM
Shipping Width	325MM, 32.5CM
Shipping Depth	565MM, 56.5CM

## Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6meters

## Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

## Recently viewed



APC Easy UPS On-Line  
SRV RM Extended R  
SRV6KRIL

[Back to top](#)



