



APC Smart-UPS C 1500VA LCD 230V with SmartConnect

SMC1500IC

Call for More Information


- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Documentation CD, USB cable

Output	
Output power capacity	900Watts / 1.5kVA
Max Configurable Power (Watts)	900Watts / 1.5kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup) (2) IEC Jumpers (Battery Backup)
Transfer Time	6ms typical : 10ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	180 - 287V
Input voltage adjustable range for mains operation	170 - 300V
Other Input Voltages	220, 240

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	RBC6 
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

Surge Protection and Filtering	
Surge energy rating	459Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	219MM, 21.9CM
Maximum Width	171MM, 17.1CM
Maximum Depth	439MM, 43.9CM
Net Weight	20.1KG
Shipping weight	22.64KG
Shipping Height	330MM, 33.0CM
Shipping Width	330MM, 33.0CM
Shipping Depth	590MM, 59.0CM
Color	Black
Master Carton Units	1.0
Units per Pallet	18.0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	135.0BTU/hr

Conformance	
Approvals	C-tick, CE, CSA, GOST, UL 1778, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Other Environmental Compliance	China RoHS

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.