



SRV2KIL



High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions

Includes: CD with software, USB cable, User Manual

Technical Specifications

Output

Output power capacity	1.6kWatts / 2.0kVA
Max Configurable Power (Watts)	1.6kWatts / 2.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	3%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(4) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 280V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4hour(s)
Efficiency	View Efficiency Graph

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous

[Back to top](#)



Surge Protection and Filtering

Surge energy rating	600Joules
----------------------------	-----------

Physical

Maximum Height	238MM, 23.8CM
-----------------------	---------------

Maximum Width	145MM, 14.5CM
----------------------	---------------

Maximum Depth	400MM, 40.0CM
----------------------	---------------

Net Weight	16.8KG
-------------------	--------

Shipping weight	18.1KG
------------------------	--------

Shipping Height	355MM, 35.5CM
------------------------	---------------

Shipping Width	235MM, 23.5CM
-----------------------	---------------

Shipping Depth	525MM, 52.5CM
-----------------------	---------------

Environmental

Operating Temperature	0 - 40 °C
------------------------------	-----------

Operating Relative Humidity	0 - 95 (non-condensing) %
------------------------------------	---------------------------

Operating Elevation	0-3000meters
----------------------------	--------------

Storage Temperature	-20 - 50 °C
----------------------------	-------------

Storage Relative Humidity	0 - 95 (non-condensing) %
----------------------------------	---------------------------

Storage Elevation	0-14763.6meters
--------------------------	-----------------

Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
------------------	----------------------------------

Standard warranty	2 years repair or replace
--------------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
-------------	-----------

REACH	REACH: Contains SVHCs
--------------	-----------------------

Recently viewed



APC Easy UPS RAIL KIT,
900MM
SRVRK2

[Back to top](#)



