



APC SMART-UPS SRT LI-ION 3000VA RM 230V NETWORK CARD

New

SRTL3000RMXLI-NC

Call for More Information

- High density, double-conversion on-line power protection with scalable runtime
- Includes: CD with software, Comms cable, Documentation CD, Installation guide, Removable support feet, USB cable, Warranty card

Output	
Output power capacity	2.7kWatts / 3.0kVA
Max Configurable Power (Watts)	2.7kWatts / 3.0kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave
Output Connections	(2) IEC 320 C19 (Battery Backup) (6) IEC 320 C13 (Battery Backup)
Bypass	Built-in Bypass

Input	
Nominal Input Voltage	230V
Input frequency	40 - 70 Hz (auto sensing)
Input Connections	British BS1363A, IEC-320 C20, Schuko CEE 7/EU1-16P
Cord Length	1.83meters
Input voltage range for main operations	50-150 (40% Load), 80 - 150V
Number of Power Cords	1
Other Input Voltages	220, 240

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Batteries & Runtime	
Battery type	Li-ion
Typical recharge time	4hour(s)
Expected Battery Life (years)	5 - 10
Extendable Run Time	1
Extended Run Options	APC-SMART-UPS-SRT-LI-ION-3000VA-RM-230V-NETWORK-CARD (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Pre-Installed SmartSlot™ Cards	AP9631 (Available in Technical Tab on site)
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering	
Surge energy rating	432Joules

Physical	
Maximum Height	128MM, 12.8CM
Maximum Width	432MM, 43.2CM
Maximum Depth	611MM, 61.1CM
Rack Height	3U
Net Weight	30.5KG
Shipping weight	41.4KG
Shipping Height	245MM, 24.5CM
Shipping Width	600MM, 60.0CM
Shipping Depth	870MM, 87.0CM
Color	Black
Units per Pallet	12.0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	50.0dBA
Online thermal dissipation	317.0BTU/hr
Protection Class	IP 20

Conformance	
Approvals	CE, EAC
Standard warranty	5 year repair or replace

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.