



# 2494L 23.8-inch LCD

Open-Frame Touchscreen



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 2494L 23.8-inch open-frame touch display features a thin and compact state-of-the-art design, with energy-saving and low-heat LED panels. Available with IntelliTouch (SAW) or TouchPro (PCAP) touch technologies, the 2494L offers the versatility needed for commercial kiosk applications from industrial automation and gaming to self-service and retail.

Featuring a brilliant wide viewing angle panel, Elo's open frames can be mounted in landscape, portrait, and face-up orientations providing optimal flexibility for integrating in any table, kiosk, or cabinet design. With proven Elo expertise and reliability built in, the industrial-grade displays provide outstanding image clarity and light transmissivity as well as stable, drift-free operation for accurate touch responses.

**Choice of touch technology:**  
Standard bezel: IntelliTouch® SAW or IntelliTouch Dual-Touch SAW  
Zero-bezel: TouchPro® PCAP

**Elo's TouchPro PCAP offers:**

- 10-touch capability that passes UL-60950, IK-07 impact testing and GLI ESD 27kV air / 8kV contact
- OSD enabled touch thru with up to 6mm of additional coverglass for increased durability & protection

**Video Interfaces: HDMI, VGA & Display Port**

## 2494L 23.8-inch Open-Frame Touch

| Specifications              |   |
|-----------------------------|---|
| Model                       | 2494L   |
| Color                       | Black   |
| Active Display Area         | 20.75" x 11.67" / 527.04mm x 296.46mm   |
| Diagonal                    | 23.8"   |
| Aspect Ratio                | 16:9  |
| Dimensions                  | Bezel: 22.14" x 12.86" x 1.64" / 562.4mm x 326.6mm x 41.7mm<br>PCAP: 22.41" x 13.43" x 1.46" / 569.2mm x 341.1mm x 37mm   |
| Native Resolution           | 1920x1080 50, 60Hz  |
| Other Supported Resolutions | 640x480 60Hz; 720x400 70Hz; 800x500, 60Hz; 800x600 56, 60Hz; 1024x768 60Hz; 1280x800 60Hz; 1280x1024 60Hz; 1366x768 60Hz, 60Hz RB; 1440x900 60Hz, 60Hz RB; 1680x1050 60Hz, 60Hz RB; 1920x1080 50, 60Hz  |
| Number of Colors            | 16.7 million  |
| Number of Touches           | Single-touch, dual-touch and 10-touch   |
| Brightness (typical)        | LCD panel: 250 nits; IntelliTouch: 225 nits; TouchPro PCAP: 225 nits  |
| Response (typical)          | 16 msec   |
| Viewing Angle               | Horizontal: 89°/178°; Vertical: 89°/178°  |
| Contrast Ratio              | 3000:1  |
| On-Screen Display           | Accessible through switches on the unit's tethered OSD Control box.<br>Controls: Menu, Up, Down, Select, Power<br>Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through (TouchPro PCAP only)<br>Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese<br>Lockouts: OSD, Power |
| I/O Ports                   | Serial port (Only available for IntelliTouch and IntelliTouch ZB), USB TypeB, RJ45 for OSD remote key, VGA, HDMI, DisplayPort, 12V D/C in   |
| Video                       | HDMI V1.3 Type A receptacle for HDMI input<br>Analog VGA on Female DB-15 connector<br>DisplayPort V1.1a - Supports later versions of DisplayPort video input<br>Input Video Horizontal Sync frequency range: 30 - 82KHz / Input Video Vertical Sync (frame rate) frequency range: 50-75Hz   |
| Power                       | External DC - Optional power brick (sold separately)<br>Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth)<br>Monitor input power signal specifications: 12VDC +/- 5%<br>Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) barrel length)  |
| Power Consumption           | Monitor + Power Brick - ON: 27.3W; SLEEP FROM PC: 1.5W; OFF: 0.5W   |
| Temperature                 | Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)  |
| Humidity                    | Operating: 20% to 80%; Storage: 10% to 95%  |
| Weight                      | Unpackaged: 14.1 lbs / 6.39 kg; Packaged: 19.3 lbs / 8.75 kg  |
| Shipping Dimensions         | 27.24" x 17.8" x 7.48" / 692mm x 452mm x 190mm  |
| Mounting Options            | 200mm x 100mm VESA mount on rear of unit; 4 Hole mounting interface on all four sides. (IntelliTouch/IntelliTouch Dual-touch Models); Side mount with included "L" brackets (IntelliTouch/IntelliTouch Dual-touch Models); Front mount with optional bezel kit (IntelliTouch/IntelliTouch Dual-touch Models); Flush mount with included brackets (TouchPro PCAP Models)   |
| Warranty                    | 3 years standard  |
| MTBF                        | 50,000 hours demonstrated   |
| Agency Approvals            | UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; RoHS, China RoHS, WEEE   |
| Compliance                  | TouchPro PCAP only - GLI 27 kV air / 8 kV contact ESD compliant; UL 60950 ball-drop compliant; IK07 impact compliant  |
| What's in the Box           | HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, Quick Install Guide; For Zero-Bezel Models: Flush Mount Brackets w/Screws; For Bezeled Models: "L" (Side Mount) Brackets w/Screws, EEL Label, Japan Class-B TM info sheet   |

## Ordering Information

| Model | Part Number | Part Description           | Technology              | Interface           | Surface Treatment | Video Interface         |
|-------|-------------|----------------------------|-------------------------|---------------------|-------------------|-------------------------|
| 2494L | E146641     | ET2494L-2UWC-0-MT-ZB-NPB-G | TouchPro PCAP           | USB 2.0             | Clear             | HDMI, VGA & DisplayPort |
|       | E329825     | ET2494L-8UWB-0-DT-NPB-G    | IntelliTouch Dual-Touch | USB 2.0             | Clear             | HDMI, VGA & DisplayPort |
|       | E330019     | ET2494L-8CWB-0-ST-NPB-G    | IntelliTouch            | Dual serial/USB 2.0 | Clear             | HDMI, VGA & DisplayPort |

## Extended Warranty Options

| Part Number | Description                    |
|-------------|--------------------------------|
| E898247     | 4 Year Warranty Coverage       |
| E898449     | 5 Year Warranty Coverage       |
| E898648     | 3 Year Warranty Coverage + AUR |
| E894921     | 4 Year Warranty Coverage + AUR |
| E895125     | 5 Year Warranty Coverage + AUR |

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
[EMEA.Sales@elotouch.com](mailto:EMEA.Sales@elotouch.com)

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
[www.elotouch.com.cn](http://www.elotouch.com.cn)

### Latin America

Tel +52 55 2281-6958  
[elosales.latam@elotouch.com](mailto:elosales.latam@elotouch.com)

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.  
© 2020 Elo Touch Solutions, Inc. All rights reserved. 20021AES00048

