



BR1200SI

High Performance Computer and Electronics UPS for Premium Power Protection

Includes: USB cable, User Manual



Technical Specifications

Output

Max Configurable Power (Watts)	720Watts / 1.2kVA
Output Frequency (sync to mains)	50/60 Hz +/-1 Hz
Topology	Line Interactive

Input

Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input voltage range for main operations	176 - 294V

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16hour(s)
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	204
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	509Joules
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection
Filtering	Full time multi-pole noise filtering :10% of IEEE surge let-through : zero clamping response time: instantaneous

Physical

Maximum Height	260MM, 26.0CM
Maximum Width	100MM, 10.0CM
Maximum Depth	368MM, 36.8CM
Net Weight	11.7KG
Shipping weight	13.35KG
Shipping Height	359MM, 35.9CM
Shipping Width	223MM, 22.3CM
Shipping Depth	482MM, 48.2CM
Color	Black
Master Carton Units	1.0
Master Carton Weight	14.21
SCC Codes	1073130434689 7

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	16.0BTU/hr

Conformance

Approvals	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI
Equipment protection policy	Lifetime : 200000 AUD, Lifetime : 150000 Euros, Lifetime : 75000 GBP
Standard warranty	2 years repair or replace, 3 years repair or replace for European Union countries

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Sign up

WHO WE ARE

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

CONNECT WITH US

[Press](#)

[APC Blog](#)

[Schneider Electric Data Centre Blog](#)

[Contact Us](#)

FIND A RESELLER

Find

CATALOG KEYCODE

Go



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

2020, APC by Schneider Electric